

HS-1873T SERIES



Materials






Sprockets



Applications

Plate Materials: POM-DP,POM-LF

Base Chain Material: Carbon steel, Stainless steel



Dimension	mm	inches
P	19.05	0.750
M	32.0	1.260
Z	11.91	0.459
H	24.5	0.965
T	20.6	0.787
F	14.3	0.563
N	55.0	2.165
E	12.7	0.472
GC(Straight)	33.3	1.311
GC(Curve)	34.6	1.362

HS-1873T (Side Flexing Plastic Chain)

CHARACTERISTICS

	Width W		Working Load		Radius		Reverse Radius		Weight (kg/m)
	(mm)	(inch)	N(21°C)	lbs(21°C)	(mm)	(inch)	(mm)	(inch)	
HS-1873T-K325	82.6	3.25	3400	765	356	14.0	305	24.0	2.10
HS-1873T-K450	114.3	4.50	3400	765	356	14.0	305	24.0	2.26
HS-1873T-K600	152.4	6.00	3400	765	475	18.0	305	24.0	2.41
HS-1873T-K750	190.5	7.50	3400	765	475	18.0	305	24.0	2.56
HS-1873T-K1000	254.0	10.00	3400	765	475	18.0	305	24.0	2.78
HS-1873T-K1200	304.8	12.00	3400	765	610	24.0	305	24.0	3.00

*The above tensile force is for Carbon steel, Please consult our engineer for that of Stainless steel.